



UNIVERSAL PUMP



Non contractual photo

INTRODUCTION

The **Universal Pump** has a ceramic mechanical seal and can transfer fluids such as coolants and lubricants or can be used to circulate internal cleaning products into refrigeration and heat transfer circuits. It is suitable for use with Facilisolv®, Désoxydant P and Dispersant D, as well as SolRnett cleaning products.

Rinse the pump between different uses.

Not suitable for flammable liquids or products.

The **Universal Pump** is made up of two elements.

The F430 PP plunger body is screwed on to the F417 electric by a single nut, making it easier to dismantle.

The plunger body, made from an external hose and a reinforced steel tube with a waterproof mechanical part, completely empties when stopped.

It is fixed to the metal drums by an optional G2 screw nut.

FEATURES

Universal pump		
Maximum viscosity	800 (mPas)	
Discharge outputs and heights	Output (l/min)	Height (m)
	80	0
	40	7
	<1	12

Polypropylene Plunger Body	
Outlet connector	DN25
Maximum temperature	50°C
External diameter	40 mm
F430PP-700 : length 700 mm - weight 1.1kg	
F430PP-1000 : length 1m - weight 1.4kg	

F417 Electric Motor	
Power	450 W
Voltage	240 V
Frequency	50 Hz
Weight	2.4 kg
IP24 Protection– Circuit breaker switch	
Supply cable length 5m	

The information contained in this product sheet is the result of our studies and experience. It is provided in good faith, but should not, under any circumstance, be taken to constitute a guarantee on our part or an assumption of our responsibility. This is particularly the case when third party rights are at stake or in situations where a user of one of our products fails to observe applicable regulations.

